

- 1. ANGLE A SHALL BE BETWEEN 45 DEGREES AND 9D DEGREES AND D SHALL BE 24 INCHES DR LESS. FOR SMALLER VALUES OF A AND LARGER VALUES OF D, USE APPROPRIATE STANDARD STRUCTURE.
- 2. IN NO CASE SHALL THE OUTSIDE DIAMETER OF THE INLET PIPE EXCEED ONE-HALF THE INSIDE DIAMETER OF THE MAIN STORM DRAIN.
- 3. CENTER LINE OF INLET SHALL BE ON RADIUS OF MAIN STORM DRAIN EXCEPT WHERE ELEVATION S IS SHOWN ON PROJECT DRAWINGS.
- 4. THE OPENING INTO MAIN STORM DRAIN SHALL BE THE OUTSIDE DIAMETER OF THE INLET PIPE PLUS ONE INCH MINIMUM OR 3 INCH MAXIMUM.
- 5. ALL CORRUGATED METAL PIPE AND FITTINGS SHALL BE GALVANIZED.
- 6. IF ANGLE B IS 45 DEGREES OR LESS, USE CASE 1, IF ANGLE B IS GREATER THAN 45 DEGREES, USE CASE 2.
- 7. BURN OR CHIP END OF CONNECTOR PIPE FLUSH WITH INNER SURFACE OF MAIN LINE PIPE. ROUND EDGE OF CONCRETE PIPE OR REINFORCED CONCRETE PIPE.
- 8. STATION SPECIFIED ON DRAWINGS APPLIES AT THE INTERSECTION OF INSIDE WALL OF MAIN STORM DRAIN AND CENTER LINE OF INLET PIPE.

NOTES: CASE 3

DATE

님

젊

- CONNECTIONS TO PIPES 21 INCHES DR LESS IN DIAMETER WITHOUT JUNCTION STRUCTURES OR PRECAST Y BRANCHES SHALL BE MADE WITH SADDLES.
- 2. TRIM OR CUT SADDLE TO FIT SNUGLY OVER THE OUTSIDE OF THE MAIN PIPE, AND SO ITS AXIS WILL BE ON THE LINE AND GRADE OF THE CONNECTING PIPE.
- 3. THE OPENING INTO THE PIPE SHALL BE CUT AND TRIMMED TO FIT THE SADDLE SO THAT NO PART WILL PROJECT WITHIN THE BORE OF THE SADDLE PIPE.
- 4. THE CONNECTING PIPE SHALL BE SUPPORTED AS SHOWN IN CASES 1 AND 2.

