

REV.	APPR. BY	DATE

REV.	APPR. BY	DATE
	Sheet Added 10/02/17	



R30B (CA) – MODIFIED

ENGLISH UNITS

A	B	C	D	E	F	G	H	J	K
12	18	.25	2.5	3	6E	2	.75C	1.5C	2C

L	M	N	O	P	Q	R	S	T	U	V
1	1C	.45C	.5	.5C	10.5	4.5	3.625	.875	1.5	.75

COLORS: BORDER, CIRCLE, DIAGONAL & LEGEND – RED (RETROREFLECTIVE)
LETTER P – BLACK
BACKGROUND – WHITE (RETROREFLECTIVE)

NOTES:

- SIGN SHALL BE IN ACCORDANCE WITH MUTCD R30B (CA).
- SIGN SHALL BE $\frac{1}{8}$ " FLAT CUT OUT ALUMINUM PANEL.
- SURFACE SHALL BE COVERED WITH 3M DIAMOND GRADE CUBE REFLECTIVE 4090 SHEETING WITH COLORS SCREENED PRINTED AND APPLY 1160A PROTECTIVE OVERLAY FILM FOR A MATCHED COMPONENT SYSTEM WARRANTY.
- TEXT SHALL BE NORMALLY UPPERCASE LETTERS PER FHWA STANDARD ALPHABETS SERIES.
- SIGNS MUST BE INSTALLED @ APPROXIMATELY 250' INTERVAL.
- SIGN POST SHALL BE PER CITY STD PLATE NO. 203, AND MAY BE MOUNTED ON EXISTING LIGHT POLE/OR STRUCTURE WHENEVER PRACTICAL.
- EXACT QUANTITY & ON SITE PLACEMENT OF EACH PANEL TO BE DETERMINED PRIOR TO FABRICATION.
- VERIFY ALL EXISTING POLE CONDITIONS & REQUIREMENTS FOR NEW POLES PRIOR TO FABRICATION.
- DETERMINE & VERIFY EXACT ROUTINE SWEEPING SCHEDULES WITH THE PUBLIC WORKS STREET DIVISION PRIOR TO FABRICATION OF SIGNS.



STREET SWEEPING SIGN

DRAWN: C. GIRON | CKD.: A. WITHANAGE

Department of Public Works

APPR.

Robert Hearne
 ROBERT HEARNE, PE

STANDARD PLAN
2002

PLATE 209

SHEET 1 OF 1